



Plant: 15000

Order#: 16150704

Line#: 001

Booking#: 168883

Booking Rev#: 1

Dealer : GREAT DANE TRAILERS (NASHVILLE)

Date : 06/15/2015

Dealer # : 90040

Contact : Turner Skipper

Dealer P.O :

Customer : R.E. WEST INC (ASHLAND CITY,TN) TRL
14 BLUGRASS DRIVE
ASHLAND CITY, TN 37015

Customer # : 257019

Customer P.O :

Code : 011915

LOM : MP

Revision : 5

Quantity : 50

Production Schedule

LOM	QTY	WEEK	EST. COMPLETION
MP	50	1523	06/26/2015

Vin Number(s) : GB707845-894

Unit Number(s) :

Sales Lock Date : 03/11/2015

Customer Furnished Date : 06/01/2015

Order Start Date : 06/08/2015

Product Data

A0500700 - Small Tire Drop

CDS-1319-01053

Serial Plate

Serial Plate - Canadian and U.S. Cert. Plate

Miscellaneous Text - None

Geometric Dimensions

Overall Height - 13' 6"

Overall Length - 53' 0"

Overall Width - 102.36"

Upper Coupler Height - 46"

King Pin Location - 36" from Nose

Drop Depth - 14"

Upper Deck Length - 122.25" Nose to Face of Drop

Miscellaneous Text - None

Front Exterior and Structure

Front Corner - 6" Radius

Front Corner Sheet - Aluminum, 0.050"

Radius Corner Protectors - Aluminum Tread Plate 0.13" x18" Below Front Top Rail (Canadian Requirement)

Front Sheets - Aluminum, 0.050"

Front Upright - Six (6) 16ga STL, 2.5" Hats

Front Vent - None

Anti Nose-Dive Device - None

Miscellaneous Text - Tire carrier mounted at center of exterior frontwall for 17.5 spare tire. Bottom of tire carrier to be installed at 10" from bottom of front bottom rail. Install C.F. tire and wheel in exterior frontwall tire carrier

Electrical Connector and Gladhand Location

Electrical Connector And Gladhand Location - Offset Roadside, Overlaid

Hose couplers (gladhands) - Great Dane Control and Supply with Red / Blue Urethane Seals

Standard Document Holder - None

Additional Manifest Box - Penz #10-03 Aluminum with Grote #4342 Registration Holder

Additional Manifest Box Location - Front, Lower Roadside

Miscellaneous Text - None

Side Exterior and Structural

Side Sheet Material - Aluminum, 0.050"

Side Sheet Texture - Flat

Bottom Rail Fasteners - .38" Aluminum Rivets

Side Upright Type - Logistic, 0.83" Sgl-Punch "A" (14 Gauge) (No Side Doors Allowed)

Side Upright Locations - 24" Centers

Extra Side Uprights - None

Side Skylight Quantity - (3) Double-hole on roadside, (2) Double-hole on curbside, staggered.

Side Skylight Location - Staggered roadside / curbside

Rub Rail Type, Side - Extruded Aluminum Rub-Rails, Two (2)

Rub Rail Location - Install per approved engineering drawing

Protection Package, External (Lift Pads) - None

Miscellaneous Text - None

Side Doors

===== Quantity of Side Doors (Area 'C') (Ahead Of Landing Gear) ===== - None

===== First Curbside Side Door Behind Landing Gear ===== - None

===== Second Curbside Side Door Behind Landing Gear ===== - None

===== First Roadside Side Door Behind Landing Gear ===== - None

===== Second Roadside Side Door Behind Landing Gear ===== - None

Miscellaneous Text - None

Rear Exterior and Structural

Rear Frame Type And Material - Stainless Steel Swing Door Comb-type Frame

Rear Frame Header - 2" Narrow Header without Rain Deflectors

Rear Impact Guard - Stainless Steel Bumper, Fully Welded

Dock Lock Bracing - None

Rear Bumpers - Laminated bumpers

Rear Bottom Rail Reinforcing - None

Tag Bracket Location - Standard

License Plate Installation - Customer Furnished License Plate to be Installed

Type of Rear Door - 0.50" Composite Swing Door, Dual-Seal Gaskets, Galvanized Steel Cover Sheet

Lock Rods - 2 per Rear Door

Hinges per door - 5 per Rear Door

Rear Door Holdback - S-Link

Rear Door Vent - None

Hazardous Material Placards - None

Miscellaneous Text - Install Customer Furnished SmartTruck "Top Kit ONLY"

Roof Options

Roof Bows - 1" Galvanized Steel, Alternating 12"/24" centers

Roof Sheet - Aluminum

Miscellaneous Text - None

Interior Lining/Scuffs/Floors

Rows of Side Scuffband - 1 Row

Type of Side Scuffband (Row One) - 12" Galvanized Steel, 18 Gauge

Side Scuffband Location (Row One) - Install At floor level, scuffband not to extend on upper deck.

Side Scuffband Position (Row One) - No Lining behind Scuff band, Lining up to top rail

Rows of Front Scuffband - None

Type of Floor - Hardwood, Lam., 1.12" Havco Fusion Composite

Quantity of Wood Floor Screws - 3 Screws per Board

Threshold Plate - Steel Diamondette, 0.125" x 15"

Hardwood Floor Finish - Havco Fusion floor with "Floor Sheild" finish by Havco.

Floor Cargo Restraint Type - None

Front Lining - SSL, 0.25" Natural Color

Side Lining - SSL Natural Color, 0.25" Full Height

Ceiling Lining - .100" x full width PunctureGuard

Unit Numbers on Lining - None

Sidewall Cargo Restraint - None

Quantity of Rows of Logistics Track - None

Miscellaneous Text - None

Understructure Forward and Bay Assembly

Upper Coupler Type - 3.50" Joggled Upper Coupler

Bottom Plate Thickness - 0.31" with Stainless Rolled-Lip

Landing Gear - Jost A441 Magnum, No-Lube

Landing Gear Foot / Shoe Type - 10" X 10" Cushion Foot

Landing Gear Handle Location - Roadside

Landing Gear Lube System - No Special Lube-System

Tire Carrier - No Tire Carrier

Crossmembers Ahead of Landing Gear - Steel Hat type on 12

Front Tire Protector Plates - 12 ga. Galvanized steel 22" X 48"

Bay Area Crossmembers - 4" Steel I-Beam on 12" Centers

URG Crossmembers - 4" Wheel-Pans Over Tandem Axle Beneath Floor and 4" Steel I-Beam on 12 " Centers

Extra Crossmembers at Rear - 8" centers Last 4' of Body (1 extra typical)

Miscellaneous Text - Install Power Packer Power Gear #100 Series with auto booster and cover plate located between axle on a fixed bogie. Install control box behind tandem located 3' from ICC bumper to center of box

Suspensions

Undercarriage Design - Tandem Axle, Fixed Spring Suspension, 49" Axle Centers

Model of Suspension - Hutchens H9700 Hangers

Bogie Location - Location to be California Legal

Pintlehook - Without Pintle Hook

Walkramp at Rear - None

Dump Valve - no dump valve due to spring suspension

Miscellaneous Text - None

Axles

Axle Type - Meritor TP Parallel Spindle .62" Wall

Brake Size - 12.25" x 7.50" (Not available w/ Intraax)

Brake Actuators - Great Dane Standard 3.0" Long Stroke

Brake Lining - Standard Brake Lining

Brake Shoe Type - Q-Plus (Meritor Extended Service)

Brake Adjusters - Due to a supply issues with Meritor the slack adjusters we will be using will be Haldex ILO. This will be done with no additional charge per Cory Lookebill.

Supplemental Brake Stroke Indicator - None

Dust Shield Type - None

Tire-Inflation-System/Tire/Wheel Options - Install only Customer Furnished Doran Smartlink Tire Pressure Monitoring system per RE West specs. Contact Todd Thornicroft: 216-406-3733, thornicroft_todd@doranmfg.com

Axle System Lube Type - None

Miscellaneous Text - None

Brake/Mudflap

Anti-Lock Brakes - Wabco 4S/2M Easy Stop

Optional Diagnostic Cable - None

Brake Valves - Sealco

Air-Tank Drain Valve - Manual Roadside Pull Cable

Mudflaps - Great Dane, Smooth Black with Logo

Mudflap Quantity/Bracket Material - 1-Pair

Mudflap Mounting Location - On Crossmember

Miscellaneous Text - Mudflaps to have 10" clearance from ground to bottom of mudflap.

Tires/Wheels/H And D

Rim/Disc Wheel Size - 17.5" X 6.75"

Hub/Wheel And Drum - Webb Hub Piloted Universal 8 Stud Hub with Webb Outboard Cast Drums

Brake Drum Balancing - None-Standard

Wheel Type - 17.5" Steel Disc Wheel, Hub Piloted, 4HH

Wheel/Rim Vendor - Accuride

Wheel Stud Options - Standard

Wheel Spacer (Corrosion Barrier) - None

Tire Size - 245/70R 17.5

Tire Brand - Michelin Energy XTA2 (J)

Spare Tire - Furnish (1) 245/70 R17.5 Michelin Energy XTA2. To be loaded on exterior frontwall spare tire carrier.

Miscellaneous Text - None

Axle End Condition

Wheel Seals - Platinum-Plus Performance Package
Axle Spindle Nuts - Pro-Torq Spindle Nut
Hubcaps - Aluminum Sentinel
Wheel Lubricant - Chevron Delo SF Synthetic Grease
Hubodometer - None
Miscellaneous Text - None

Electrical Wiring/Lights

Exterior Light Package - All Lights LED, Grote Long Life Light System, Grote MicroNova Dot Lamps
Electrical Connector - Great Dane Standard 7-Way Split Pin
Front Top Rail Lights - 1 Top Mounted on Front Corner at 45 Degrees, Roadside and Curbside (Canadian Requirement)
Buckplate Light Type - Grote Series 40, LED Flange Mount
Buckplate Lights Qty and Loc - 2 Each Side
Stainless Theft-Resistant Flange for LED Lamps - Installed on Buckplate lamps with Stainless Rivets
Rear Header Light Locations - Center Cluster of 3 Lamps with Dual Intensity Brake Indication, with 1 Lamp Each Side Outboard Corner with Dual Intensity Turn Indication
Top and Bottom Side Marker Lamps/Location - Standard Lamp Package, 1 Each Side Top Rail @ Front, 1 Each Side Mid-ship Combination (req'd on trlrs 30' and over), 1 Each Side Bottom Rail @ Rear
Midship Turn Signal - Grote LED Combination Turn and Clearance
Location of Turn Signal - Roadside and Curbside, Center of Trailer
Installation of Turn Signal - Install Below Bottom Rail
Supplemental Turn Signal - None
Miscellaneous Text - None

Electrical (Interior)

Dome Light Quantity - None
Quantity of Spotlights - None
Miscellaneous Text - None

Finish/Paint/Decals

Front Finish - Pre-Painted Black
Side Finish - Pre-Painted Black
Rivet Color - Unpainted
Rear Frame Finish - Stainless Steel Rear Frame Stainless Steel Impact Guard
Rear Door Finish - Pre-Painted Black
Installation Of Customer Decals - Install Customer Furnished Decals Per R.E. West Specs.
Undercarriage Finish - Black CorroGuard coating (corrosion-resistant)
Wheel Finish - White Powder Coat
Upper Coupler Finish - Great Dane Standard Coating
Landing Gear Finish - Black Undercoat
Upper Running Gear Finish - Great Dane Standard Coating
Conspicuity Treatment Location - Great Dane on Bottom Rail
Manufacturers Logo Installation - Red Logos
Unit Numbers (Exterior) - Install Customer Furnished unit numbers.
Paint Loadline - None
Top Rail Paint - None
Bottom Rail Paint - None
Additional Undercoat - None
Miscellaneous Text - Stencil "RE West" and Unit # on interior roadside and curbside rear just inside rear door. Unit Number to be stenciled under RE West. Also paint a black 2" line at 48 ft. on the side wall full height floor to ceiling. This will include painting over the scuff band.

Insulation

Front Insulation - None
Side Insulation - None
Roof Insulation - None
Miscellaneous Text - None

Controlled Temperature Unit

Type of Nose Mounted Unit - None
Miscellaneous Text - None
